

GOODYEAR DCT

Dual Clutch Transmission Fluid

EN High performance dual clutch transmission fluid (DCTF) intended to the specific wear and friction requirements in modern dual clutch transmissions with high torques. Not suitable for use in conventional automatic transmissions and continuously variable transmissions.

LT Efektyvus dvigubos sankabos transmisijos skystis (DCTF), skirtas specialiems modernių dvigubos sankabos transmisijų su dideliais sukimo momentais dėvėjimo ir trynimo reikalavimams. Netinkamas naudoti automatinėms transmisijoms su laipsniais ir be laipsnėms transmisijoms.

LV Augstas veiktspējas dubultā sajūga transmisijas šķidrums (DCTF) pielāgots īpašajām nodiluma un berzes prasībām mūsdienu divsajūgu transmisijās ar augstu griezes momentu. Nav piemērots lietošanai parastajās automātiskajās transmisijās un bezipakāpju variatora transmisijās.

EE Suure jõudlusega topeltsiduriga käigukasti õli (DCTF), mis vastab tänapäeva suure pöördemomendiga topeltsiduriga käigukastide spetsiifilistele kulumis- ja hõõrdumismõuetele. Ei sobi kasutamiseks tavapärastes automaatkäigukastides ja astmeteta käigukastides.

BMW DCTF-1, DCTF-1+, DCTF-2
BMW Drivelogic 7-speed (Getrag)
BMW 6-speed DCT
BMW MTF LT-5, 83 22 2 167
Borg Warner
Bugatti Veyron
BYD DCTs, Q/BYD-A1909.0058-2013
Chrysler 68044345 EA & GA
Chrysler Powershift 6-speed (Getrag)
Fiat 9.55550-HE2, -MZ6
Ford / Nissan Powershift 6-speed (GFT)

Ford WSS-M2C 936 A
Ford WSS-M2C 200-D2/XT-11-QDC
Ford WSS-M2C 218-A1, Ford F-DC
Mitsubishi MZ320065 DiaQueen SSTF-1
Peugeot / Citroen DCS 6-speed (GFT)
PSA 9734.S2
Porsche 999.917.080.01
Renault EDC 6-speed (Getrag), EDC-7
Renault DC4 (BOT 450), DW5, DW6
Volvo Powershift 6-speed (GFT)
Lynk & Co. 01 (Plug-in Hybrid & Hybrid eL SUV)

Volvo 1161838, 1161839
Volvo Dual Clutch Oil D1, D2
Subaru Lineartronic chain CVT and CVT II Fluid
VW G 052 536, 055 536
VW (Audi, Seat, Skoda) 6-speed
VW/Audi TL 52 182/G 052 182 A2 or A6 (fluid)
VW/TL 52 529/G 052 529 A2/A6/ DSG7 = S-Tronic 7
VW (Audi, Seat, Skoda) 7-speed
VW / Audi G 055 529
ZF / Porsche Oil #999.917.080.00
VW Golf GTE DQ400E

Typical data	Method	Value
Density at 15°C, g/cm ³	ASTM D 1298	0,847
Viscosity at 100°C, mm ² /s (cSt)	ASTM D 445	7,1
Viscosity index (VI)	ASTM D 2270	174
Flash point COC, °C	ASTM D 92	220
Pour point, °C	ASTM D 97	- 45

The average values are given for information, values may vary within the official limits. Safety data sheet available on request.

Packing			
1L	4L	-	208L