

GOODYEAR STOU 10W-40

Super Tractor Oil Universal

EN Multi-grade multi-purpose oil suitable for agricultural equipments like tractors and construction engines in accordance with the unit manufacturer's instructions. Super tractor oil universal (STOU) applicable in motors, transmissions, hydraulics and wet brakes of agricultural machines.

LT Daugiafunkcē, universali alyva, skirta žemēs ūkio iřrangai kaip traktoriai ir statybinių mašinų varikliui pagal iřrangos gamintojo instrukcijas. Ypatinga, universali traktorių alyva (STOU), naudojama žemēs ūkio mašinų motoruose, transmisijose, hidraulikoje ir šlapiuose stabdžiuose.

LV Daudzfunkcionāla vissezonu eļļa piemērota lauksaimniecības iekārtām, traktoriem un celtniecības dzinējiem, saskaņā ar agregāta ražotāja norādījumiem. Super tractor oil universal (STOU) eļļa izmantojama lauksaimniecības mašīnu motoros, transmisijās, hidraulikā un slapjās bremzēs.

EE Universaalne õli, mis sobib põllumajandusmasinate, nāiteks traktorite ja ehitusmasinate mootoritele seadmetootja juhiste kohaselt. Universaalne super-traktoriõli (STOU), mida kasutatakse põllumajandusmasinate mootorites, jõuülekannetes, hüdraulikasüsteemis ja märgpidurites.

SAE 10W-40 SAE 80W90 Fendt Vario MB 227.1/228.1 Allison C-4	API CG-4/CF-4/CF/SF API GL-4 Caterpillar TO-2 CNH MAT 3525/3526 SV Eaton I-280-S/M2950S	ACEA E3 SSD Hydrostatic TransFluid Ford New Holland 82009201/2/3 MF CSM M 11 35/39/43/44/45 Case MS 12 04/06/07/09	ISO VG 46÷100 HLP/HLPD/HVLP ZF TE-ML 06B/06C/06R/07B John Deere J20C/D, J27 Ford M2C 86B/C,134D,159B/C
--	--	---	---

Typical data	Method	Value
Density at 15°C, g/cm ³	ASTM D 1298	0,87
Viscosity at 100°C, mm ² /s (cSt)	ASTM D 445	13,3
Viscosity index (VI)	ASTM D 2270	152
Flash point COC, °C	ASTM D 92	240
Pour point, °C	ASTM D 97	- 38
T.B.N. (Total Base Number), mg KOH/g	ASTM D 2896	10

The average values are given for information, values may vary within the official limits. Safety data sheet available on request.

Packing			
-	5L	20L	208L