

# GOODYEAR TRUCK 15W-40

## Heavy Duty Diesel Oil (HDDO)

**EN** Multigrade SHPD type (Super High Performance Diesel) engine oil intended for heavy-duty commercial vehicle diesel engines in accordance with the vehicle manufacturer's instructions. Also suitable for passenger car diesel and gasoline engines, including turbo charged ones in accordance with the vehicle manufacturer's instructions.

**LT** Daugiafunkė SHPD tipo (itin efektyvaus dyzelio) variklio alyva, skirta sunkiuju komercinės paskirties transporto priemonių dyzeliniams varikliams pagal transporto priemonės gamintojo instrukcijas. Taip pat tinkama lengvųjų automobilių benziniams ir dyzeliniams varikliams, įskaitant su turbokompresoriumi, pagal transporto priemonės gamintojo instrukcijas.

**LV** Vissezonu SHPD tipa (Super High Performance Diesel) motoreļļa paredzēta lieljaudas komerctransporta dīzeļdzinējiem saskaņā ar transportlīdzekļa ražotāja norādījumiem. Piemērota arī vieglo automobiļu dīzeļdzinējiem un benzīna dzinējiem, tai skaitā dzinējiem ar turbokompresoru.

**EE** Universaalne SHPD-tüüpi (Super High Performance Diesel) mootoriõli, mis on ette nähtud raskeveokite diiselmootoritele sõidukitootja juhiste kohaselt. Sobib ka sõiduautode diisel- ja bensiinimootoritele, sealhulgas turbomootoritele, sõidukitootja juhiste kohaselt.

**SAE 15W-40**  
**MAN M 3275-1**

**ACEA E7**  
**MTU Type 2**

**API CI-4/SL**  
**MAN M3277**

**Volvo VDS-3**  
**MB 228.3/229.1**

Typical data	Method	Value
Density at 15°C, g/cm <sup>3</sup>	ASTM D 1298	0,882
Viscosity at 100°C, mm <sup>2</sup> /s (cSt)	ASTM D 445	14,5
Viscosity index (VI)	ASTM D 2270	135
Flash point COC, °C	ASTM D 92	235
Pour point, °C	ASTM D 97	- 33
T.B.N. (Total Base Number), mg KOH/g	ASTM D 2896	9,0

The average values are given for information, values may vary within the official limits. Safety data sheet available on request.

Packing			
-	5L	20L	208L