



Technical passport

Magna ANTIFREEZE

Ready to use automotive coolant suitable for all types of modern cooling systems in accordance with the manufacturer's instructions. Protects the cooling system at temperatures up to -36°C. Contains ethylenglycol, demineralised water, additives.

Norms

**ASTM D 3306; SAE J 1034; BS 6580 (UK);
NATO S759; CUNA NC 956-16(I); Afnor R 15/601(F)**

Approvals

**VW/Audi/Seat/Skoda TL774C MB DBL 7700 VOLVO N260
Ford ESD M97B49A GM US 6277M MAN 324
OPEL GM QL 130100 BMW N 600 69.0 Chrysler MS 9176**

| Typical Data | Units | Method | Magna ANTIFREEZE |
|---|-------------------|-------------|----------------------------------|
| Colour | - | - | green |
| Density at 20°C | g/cm ³ | ASTM D 1122 | 1,07 |
| Boiling point | °C | ASTM D 1120 | >105 |
| Pour point | °C | ASTM D 97 | -36 |
| Corrosion: Copper Brass Solder Steel Aluminum Cast iron | mg | ASTM D 1384 | 10 10 30 10 30 10 |
| Product pH | - | ASTM D 1287 | 7-9 |

Packing: 1L, 5L, 208L



Magna ANTIFREEZE is a product of the UNITED OILS LLC